

Wireless Automatic Water Level Controller WLLC-110 (for two tanks)



Transmitter
(for Overhead Tank)



Receiver
(for Underground Tank)

Technical Specifications / Features :

- Wireless interface provides cost effective, easy and maintenance free installation.
- Range / Distance cover : From Ground floor to 5-7th floor (Depending of surroundings)
- Line of sight : 0.95Km - 1.75Km
- Range indication is provided. If receiver "DATA COM" LED blinks then transmitter in the range of receiver. If LED glows steadily then transmitter is out of range of receiver.
- Detachable antenna with jack pin allows ease of handling
- Antenna length : 8-24 cm
- Sensor : Carbon sensor. It is free from oxydation and hence provides long life.
- Dry run protection for motor.
- Motor On/Off indication along with buzzer.
- Suitable for MCB starter panel
- Supply voltage : 200-270 VAC
- Output : Single Phase Motor (0.5HP to 5.0HP)
- Modes : Auto/Off/Bypass (Bypass/Manual mode helps in fault condition of controller)
- Dimension :
Transmitter - 4x3x2 inch Receiver - 6x4x3.5 inch
- Mounting - Wall mounting with screws

Doc no.: EL21011801



EMBELINK TECHNOLOGIES

18-19, Changodar Industrial Estate,
Besides Elite Conductors Ltd,
Changodar, AHMEDABAD 382213.
embelinktech@gmail.com

Wiring and Connections Diagram :

